

Mechanical	
Dimensions	99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25")
Weight	450 g (15.87 oz)
Hardware	
Total Non-Blocking Line Rate	8 Gbps
Power Consumption	8W
Power Method	54VDC, 1.1A Power Adapter
Power Supply	External 54V/60W Power Adapter
Supported Voltage Range	DC 50V to 57V
Networking Interfaces	10/100/1000 Mbps Ethernet RJ45
PoE Interfaces	PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Management Interface	Ethernet In-Band
Max PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC
LEDs	
System	Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at