

Specifications:

Dimensions	442.4 x 285 x 43.7 mm (17.42 x 11.22 x 1.72")
Weight With Rackmount Brackets	4.52 kg (9.97 lb) 4.61 kg (10.16 lb)
Interfaces Networking Management	(48) 10/100/1000 RJ45 Ports (4) 1G SFP Ethernet Ports Ethernet In-Band
Power Method	100-240VAC, 50/60 Hz, Universal Input
Power Supply	AC/DC, Internal, 240W
Supported Voltage Range	100 to 240VAC
LEDs RJ45 Data Ports SFP Data Ports	PoE; Speed/Link/Activity Link/Activity
ESD/EMP Protection	Air: ± 16 kV, Contact: ± 12 kV
Shock and Vibration	ETSI300-019-1.4 Standard
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 to 90% Noncondensing
Certifications	CE, FCC, IC
PoE	
PoE Ports 1-32 Interfaces	POE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Max. PoE Wattage per Port by PSE 802.3at	32W
Voltage Range 802.3af Mode	44-57V
Voltage Range 802.3at Mode	50-57V