

Dimensions	160 x 160 x 31.45 mm	
Weight	170g (185g with mounting)	
Network Interfaces	1x 10/100/1000 Ethernet	
Button	Reset	
Standards Wi-Fi	802.11 a / b / g / n / ac	
Method powered	Passive Power over Ethernet 24V	
Power	24V, 0.5A PoE Gigabit Adapter (not included) Max. Power consumption 6.5W	
Energy saving	Supported	
Security	WEP, WPA-PSK, WPA-TKIP, AES WPA2, 802.11i	
Certification	CE, FCC, IC	
Fixing	Wall / Ceiling (el. Installation included)	
Temperature	-10 to 70 & deg; C	
Operating humidity	5 - 95%	
2.4 GHz	2x integrated (Support for 2x2 MIMO with Spatial Diversity)	
5 GHz	2x Integrated (support for 2x2 MIMO with Spatial Diversity)	
Max. TX power	2.4 GHz, 5 GHz 20dBm, 20dBm	
VLAN 802.1Q		
Advanced QoS Per-User Rate Limiting		
Guest Traffic Isolation Supported		
WMM Voice, Video, Best Effort, and Background		
Number of simultaneous clients 200+		
Standard	Throughput	
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps	
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)	
802.11ac	6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)	
802.11b	1, 2, 5.5, 11 Mbps	
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps	