

Technical Specification:

Mechanical	
Dimensions	Ø 197 x 35 mm (Ø 7.76 x 1.38")
Weight	Without Mount: 460 g (1.01 lb) With Mount: 600 g (1.32 lb)
Enclosure Material	Plastic
Mounting Material	SGCC Steel
Weatherproofing	IP54
Hardware	
Management Interface	Ethernet, Bluetooth
Networking Interface	(1) 10/100/1000 Mbps Ethernet RJ45
Buttons	Factory Reset
LEDs	White/blue
Power Method	802.3at PoE+
Power Supply	UniFiPoESwitch 48V, 0.5A PoE Adapter (Not Included)
Supported Voltage Range	44 to 57VDC
Max. Power Consumption	13 W
Max. TX Power 2.4GHz 5GHz	22dBm 26 dBm
MIMO 2.4GHz 5GHz	2x2(ULMU-MIMO) 4 x 4 (DL/UL MU-MIMO)
Throughput Speeds 2.4GHz 5GHz	573.5Mbps 4.8 Gbps
Antenna Gain 2.4GHz 5GHz	4dBi 6 dBi
Mounting	Wall/Ceiling (Kits Included)
Operating Temperature	-30 to 60° C (-22 to 140° F)
Operating Humidity	5 - 95% Noncondensing
Certifications	CE, FCC, IC
Software	
Wi-Fi Standards	802.11a/b/g Wi-Fi 4/Wi-Fi 5/Wi-Fi 6
Wireless Security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)

BSSID	8 per Radio
VLAN	802.1Q
Advanced QoS	Per-User Rate Limiting
Guest Traffic Isolation	Supported
Concurrent Clients	300+